

WATERSTOP MASTIC

Description

Plastomeric sealing mastic, water-resistant, heat-resistant, anti-aging, permanently plastic. Applied in compression to seal the seams between proofing membrane and mechanical terminals, e.g. piping, plates, fixing profiles etc.

Features

Colours

Light grey.

Creep ISO 7390

Nil.

Application temperature

-25 ÷ +90°C

Packaging

- 310 ml Polyethylene cartridge.
- Carton with 12 cartridges, 90 cartons per pallet.
- Weight: 6.9 kg/carton approx.
- ADR land transport classification: not classified.

Standard colours

Grey.

Yield

5 × 5 mm bead	13 m/cartridge
10 × 5 mm bead	6.4 m/cartridge

Application

- Substrate must be clean, dry and uncontaminated.
- Application temperature: +10 ÷ +35°C(*).
- Not for use as external finish sealant.
- See RUBBERFUSE Division specifications and instructions.

Note: (*) Preheating is recommended if product is applied at temperatures below 10°C.

Safety regulations

- Avoid contact with the skin.
- In case of contact with eyes, rinse immediately with plenty of water.
- When using do not eat, drink or smoke.
- Wash hands with soap and water after use.
- Refer to the EC Safety Data Sheet.
- S23: do not breathe vapour/spray.

Rev. 00 (11-15)

As IMPER ITALIA srl has no control over how or where its products are supplied (e.g., over substrates, service conditions, or compliance with instructions), the company cannot accept any liability arising from the use of its product or the results obtained. IMPER ITALIA srl pursues a policy of continuous product improvement. As a result, the company reserves the right to make any necessary changes to the information contained in this publication at any time and without notice.

ISO 9001
ISO 14001
OHSAS 18001
BUREAU VERITAS
Certification



Imper Italia srl Via Volta, 8 · 10071
Frazione Mappano · Borgaro (TO) Italy
Tel (+39) 011 222.54.99 · Fax (+39) 011 222.54.80
export@imper.it · www.imper.it